

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min <sup>-1</sup> )		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>w</sub></i>	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease	Oil		
25	47	16	0.6	-	41.3	25800	30000	14000	17000	NN3005	
25	47	16	0.6	-	41.3	25800	30000	14000	17000	NN3005K	
30	55	19	1	-	48.5	31000	37000	12000	14000	NN3006	
30	55	19	1	-	48.5	31000	37000	12000	14000	NN3006K	
35	62	20	1	-	55	39500	50000	10000	12000	NN3007	
35	62	20	1	-	55	39500	50000	10000	12000	NN3007K	
40	68	21	1	-	61	43500	55500	9000	11000	NN3008	
40	68	21	1	-	61	43500	55500	9000	11000	NN3008K	
45	75	23	1	-	67.5	52000	68500	8500	10000	NN3009	
45	75	23	1	-	67.5	52000	68500	8500	10000	NN3009K	
50	80	23	1	-	72.5	53000	72500	7500	9000	NN3010	
50	80	23	1	-	72.5	53000	72500	7500	9000	NN3010K	
55	90	26	1.1	-	81	69500	96500	6700	8000	NN3011	
55	90	26	1.1	-	81	69500	96500	6700	8000	NN3011K	
60	95	26	1.1	-	86.1	73500	106000	6300	7500	NN3012	
60	95	26	1.1	-	86.1	73500	106000	6300	7500	NN3012K	
65	100	26	1.1	-	91	77000	116000	6000	7100	NN3013	
65	100	26	1.1	-	91	77000	116000	6000	7100	NN3013K	
70	110	30	1.1	-	100	97500	148000	5600	6700	NN3014	
70	110	30	1.1	-	100	97500	148000	5600	6700	NN3014K	
75	115	30	1.1	-	105	96500	149000	5300	6300	NN3015	
75	115	30	1.1	-	105	96500	149000	5300	6300	NN3015K	
80	125	34	1.1	-	113	119000	186000	4800	6000	NN3016	
80	125	34	1.1	-	113	119000	186000	4800	6000	NN3016K	
85	130	34	1.1	-	118	125000	201000	4500	5600	NN3017	
85	130	34	1.1	-	118	125000	201000	4500	5600	NN3017K	
90	140	37	1.5	-	127	143000	228000	4300	5000	NN3018	
90	140	37	1.5	-	127	143000	228000	4300	5000	NN3018K	
95	145	37	1.5	-	132	150000	246000	4000	5000	NN3019	
95	145	37	1.5	-	132	150000	246000	4000	5000	NN3019K	
100	140	40	1.1	112	-	155000	295000	4000	5000	NNU4920	
100	140	40	1.1	112	-	155000	295000	4000	5000	NNU4920K	
100	150	37	1.5	-	137	157000	265000	4000	4800	NN3020	
100	150	37	1.5	-	137	157000	265000	4000	4800	NN3020K	
105	145	40	1.1	117	-	161000	315000	3800	4800	NNU4921	
105	145	40	1.1	117	-	161000	315000	3800	4800	NNU4921K	
105	160	41	2	-	146	198000	320000	3800	4500	NN3021	
105	160	41	2	-	146	198000	320000	3800	4500	NN3021K	
110	150	40	1.1	122	-	167000	335000	3600	4500	NNU4922	
110	150	40	1.1	122	-	167000	335000	3600	4500	NNU4922K	
110	170	45	2	-	155	229000	375000	3400	4300	NN3022	
110	170	45	2	-	155	229000	375000	3400	4300	NN3022K	
120	165	45	1.1	133.5	-	183000	360000	3200	4000	NNU4924	
120	165	45	1.1	133.5	-	183000	360000	3200	4000	NNU4924K	
120	180	46	2	-	165	239000	405000	3200	3800	NN3024	

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min <sup>-1</sup> )		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>w</sub></i>	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease	Oil		
120	180	46	2	-	165	239000	405000	3200	3800	NN3024K	
130	180	50	1.5	144	-	274000	545000	3000	3800	NUU4926	
130	180	50	1.5	144	-	274000	545000	3000	3800	NUU4926K	
130	200	52	2	-	182	284000	475000	3000	3600	NN3026	
130	200	52	2	-	182	284000	475000	3000	3600	NN3026K	
140	190	50	1.5	154	-	283000	585000	2800	3600	NUU4928	
140	190	50	1.5	154	-	283000	585000	2800	3600	NUU4928K	
140	210	53	2	-	192	298000	515000	2800	3400	NN3028	
140	210	53	2	-	192	298000	515000	2800	3400	NN3028K	
150	210	60	2	167	-	350000	715000	2600	3200	NUU4930	
150	210	60	2	167	-	350000	715000	2600	3200	NUU4930K	
150	225	56	2.1	-	206	335000	585000	2600	3000	NN3030	
150	225	56	2.1	-	206	335000	585000	2600	3000	NN3030K	
160	220	60	2	177	-	365000	760000	2400	3000	NUU4932	
160	220	60	2	177	-	365000	760000	2400	3000	NUU4932K	
160	240	60	2.1	-	219	375000	660000	2400	2800	NN3032	
160	240	60	2.1	-	219	375000	660000	2400	2800	NN3032K	
170	230	60	2	187	-	375000	805000	2400	2800	NUU4934	
170	230	60	2	187	-	375000	805000	2400	2800	NUU4934K	
170	260	67	2.1	-	236	450000	805000	2200	2600	NN3034	
170	260	67	2.1	-	236	450000	805000	2200	2600	NN3034K	
180	250	69	2	200	-	480000	1020000	2200	2600	NUU4936K	
180	280	74	2.1	-	255	565000	995000	2000	2400	NN3036	
180	280	74	2.1	-	255	565000	995000	2000	2400	NN3036K	
190	260	69	2	211.5	-	485000	1060000	2000	2600	NUU4938	
190	260	69	2	211.5	-	485000	1060000	2000	2600	NUU4938K	
190	290	75	2.1	-	265	595000	1080000	2000	2400	NN3038	
190	290	75	2.1	-	265	595000	1080000	2000	2400	NN3038K	
200	280	80	2.1	223	-	570000	1220000	1900	2400	NUU4940	
200	280	80	2.1	223	-	570000	1220000	1900	2400	NUU4940K	
200	310	82	2.1	-	282	655000	1170000	1800	2200	NN3040	
200	310	82	2.1	-	282	655000	1170000	1800	2200	NN3040K	
220	300	80	2.1	243	-	600000	1330000	1700	2200	NUU4944	
220	300	80	2.1	243	-	600000	1330000	1700	2200	NUU4944K	
220	340	90	3	-	310	815000	1480000	1700	2000	NN3044	
220	340	90	3	-	310	815000	1480000	1700	2000	NN3044K	
240	320	80	2.1	263	-	625000	1450000	1600	2000	NUU4948	
240	320	80	2.1	263	-	625000	1450000	1600	2000	NUU4948K	
240	360	92	3	-	330	855000	1600000	1500	1800	NN3048	
240	360	92	3	-	330	855000	1600000	1500	1800	NN3048K	
260	360	100	2.1	289	-	935000	2100000	1400	1800	NUU4952	
260	360	100	2.1	289	-	935000	2100000	1400	1800	NUU4952K	
260	400	104	4	-	364	1030000	1920000	1400	1700	NN3052	
260	400	104	4	-	364	1030000	1920000	1400	1700	NN3052K	
280	380	100	2.1	309	-	960000	2230000	1300	1700	NUU4956	

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min <sup>-1</sup> )		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>w</sub></i>	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease	Oil		
<b>280</b>	380	100	2.1	309	-	960000	2230000	1300	1700	<b>NNU4956K</b>	
<b>280</b>	420	106	4	-	384	1080000	2080000	1300	1500	<b>NN3056</b>	
<b>280</b>	420	106	4	-	384	1080000	2080000	1300	1500	<b>NN3056K</b>	
<b>300</b>	420	118	3	336	-	1230000	2870000	1200	1500	<b>NNU4960</b>	
<b>300</b>	420	118	3	336	-	1230000	2870000	1200	1500	<b>NNU4960K</b>	
<b>300</b>	460	118	4	-	418	1290000	2460000	1200	1400	<b>NN3060</b>	
<b>300</b>	460	118	4	-	418	1290000	2460000	1200	1400	<b>NN3060K</b>	
<b>320</b>	440	118	3	356	-	1260000	3050000	1100	1400	<b>NNU4964</b>	
<b>320</b>	440	118	3	356	-	1260000	3050000	1100	1400	<b>NNU4964K</b>	
<b>320</b>	480	121	4	-	438	1350000	2670000	1100	1300	<b>NN3064</b>	
<b>320</b>	480	121	4	-	438	1350000	2670000	1100	1300	<b>NN3064K</b>	
<b>340</b>	520	133	5	-	473	1670000	3300000	1000	1200	<b>NN3068</b>	
<b>340</b>	520	133	5	-	473	1670000	3300000	1000	1200	<b>NN3068K</b>	
<b>360</b>	540	134	5	-	493	1700000	3450000	950	1200	<b>NN3072</b>	
<b>360</b>	540	134	5	-	493	1700000	3450000	950	1200	<b>NN3072K</b>	