

Boundary Dimensions (mm)						Basic Load Ratings (N)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>B</i> ₄	<i>C</i> ₄	<i>r</i> min.	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> _{0r}		
170	240	175	175	2.5	2	870000	2000000	STF170KVS24 01E	
220	340	303.5	303.5	3	3	2490000	5950000	STF220KVS34 01E	
241.478	349.148	228.6	228.6	3.3	1	1730000	4150000	STF241KVS34 51E	
244.475	327.025	193.68	193.68	3	1	1240000	3300000	STF244KVS32 51E	
254	358.775	269.875	269.875	3.3	1	2150000	5650000	STF254KVS35 51E	
266.7	355.6	230.188	228.6	3.3	1	1640000	4500000	STF266KVS35 51E	
276.225	393.7	269.875	269.875	6.4	1	2360000	6050000	STF276KVS39 51E	
279.4	393.7	269.875	269.875	6.4	1	2360000	6050000	STF279KVS39 51E	
304.648	438.048	280.99	279.4	3.3	3	2640000	6750000	STF304KVS43 51E	
304.8	419.1	269.875	269.875	6.4	1	2450000	6550000	STF304KVS41 51E	
304.902	412.648	266.7	266.7	3.3	3	2320000	6350000	STF304KVS41 52E	
343.052	457.098	254	254	3.3	1	2430000	6700000	STF343KVS45 51E	
355.6	482.6	265.112	269.875	3.3	1	2650000	7350000	STF355KVS48 51E	
406.4	546.1	288.925	288.925	6.4	1	3400000	9450000	STF406KVS54 51E	
430	575	380	380	5	1	4650000	14200000	STF430KVS57 51E	
450	595	368	368	5	4	4550000	14100000	STF450KVS59 01E	
457.2	596.9	276.225	279.4	3.3	1	3400000	9850000	STF457KVS59 51E	
482.6	615.95	330.2	330.2	6.4	4	4200000	13500000	STF482KVS61 51E	
509.948	654.924	377	379	5	1	4950000	17100000	STF509KVS65 51E	