

Thrust Bearings

└ Single-Direction Thrust Ball Bearings

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min ⁻¹)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>T</i>	<i>T</i> ₃	<i>T</i> ₄	<i>r</i> min.	<i>C</i> _a	<i>C</i> _{0a}	Grease	Oil		
10	24	9	-	-	0.3	10100	14000	6700	10000	51100	
10	26	11	-	-	0.6	12800	17100	6000	9000	51200	
10	26	-	11.6	-	0.6	12800	17100	6000	9000	53200	
10	26	-	11.6	13	0.6	12800	17100	6000	9000	53200U	
12	26	9	-	-	0.3	10400	15400	6700	10000	51101	
12	28	11	-	-	0.6	13300	19000	5600	8500	51201	
12	28	-	11.4	-	0.6	13300	19000	5600	8500	53201	
12	28	-	11.4	13	0.6	13300	19000	5600	8500	53201U	
15	28	9	-	-	0.3	10600	16800	6300	9500	51102	
15	32	12	-	-	0.6	16700	24800	5000	7500	51202	
15	32	-	13.3	-	0.6	16700	24800	5000	7500	53202	
15	32	-	13.3	15	0.6	16700	24800	5000	7500	53202U	
17	30	9	-	-	0.3	11400	19500	6000	9000	51103	
17	35	12	-	-	0.6	17300	27300	4800	7500	51203	
17	35	-	13.2	-	0.6	17300	27300	4800	7500	53203	
17	35	-	13.2	15	0.6	17300	27300	4800	7500	53203U	
20	35	10	-	-	0.3	15100	26600	5300	8000	51104	
20	40	14	-	-	0.6	22500	37500	4300	6300	51204	
20	40	-	14.7	-	0.6	22500	37500	4300	6300	53204	
20	40	-	14.7	17	0.6	22500	37500	4300	6300	53204U	
25	42	11	-	-	0.6	19700	37000	4800	7100	51105	
25	47	15	-	-	0.6	28000	50500	3800	5600	51205	
25	47	-	16.7	-	0.6	28000	50500	3800	5600	53205	
25	47	-	16.7	19	0.6	28000	50500	3800	5600	53205U	
25	52	18	-	-	1	36000	61500	3200	5000	51305	
25	52	-	19.8	-	1	36000	61500	3200	5000	53305	
25	52	-	19.8	22	1	36000	61500	3200	5000	53305U	
25	60	24	-	-	1	56000	89500	2600	4000	51405	
25	60	-	26.4	-	1	56000	89500	2600	4000	53405	
25	60	-	26.4	29	1	56000	89500	2600	4000	53405U	
30	47	11	-	-	0.6	20600	42000	4300	6700	51106	
30	52	16	-	-	0.6	29500	58000	3400	5300	51206	
30	52	-	17.8	-	0.6	29500	58000	3400	5300	53206	
30	52	-	17.8	20	0.6	29500	58000	3400	5300	53206U	
30	60	21	-	-	1	43000	78500	2800	4300	51306	
30	60	-	22.6	-	1	43000	78500	2800	4300	53306	
30	60	-	22.6	25	1	43000	78500	2800	4300	53306U	
30	70	28	-	-	1	73000	126000	2200	3400	51406	
30	70	-	30.1	-	1	73000	126000	2200	3400	53406	
30	70	-	30.1	33	1	73000	126000	2200	3400	53406U	
35	52	12	-	-	0.6	22100	49500	4000	6000	51107	
35	62	18	-	-	1	39500	78000	3000	4500	51207	
35	62	-	19.9	-	1	39500	78000	3000	4500	53207	
35	62	-	19.9	22	1	39500	78000	3000	4500	53207U	
35	68	24	-	-	1	56000	105000	2400	3800	51307	

Thrust Bearings

└ Single-Direction Thrust Ball Bearings

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min ⁻¹)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>T</i>	<i>T</i> ₃	<i>T</i> ₄	<i>r</i> min.	<i>C</i> _a	<i>C</i> _{0a}	Grease	Oil		
35	68	-	25.6	-	1	56000	105000	2400	3800	53307	
35	68	-	25.6	28	1	56000	105000	2400	3800	53307U	
35	80	32	-	-	1.1	87500	155000	2000	3000	51407	
35	80	-	34	-	1.1	87500	155000	2000	3000	53407	
35	80	-	34	37	1.1	87500	155000	2000	3000	53407U	
40	60	13	-	-	0.6	27100	63000	3600	5300	51108	
40	68	19	-	-	1	47500	98500	2800	4300	51208	
40	68	-	20.3	-	1	47500	98500	2800	4300	53208	
40	68	-	20.3	23	1	47500	98500	2800	4300	53208U	
40	78	26	-	-	1	70000	135000	2200	3400	51308	
40	78	-	28.5	-	1	70000	135000	2200	3400	53308	
40	78	-	28.5	31	1	70000	135000	2200	3400	53308U	
40	90	36	-	-	1.1	103000	188000	1700	2600	51408	
40	90	-	38.2	-	1.1	103000	188000	1700	2600	53408	
40	90	-	38.2	42	1.1	103000	188000	1700	2600	53408U	
45	65	14	-	-	0.6	28100	69000	3400	5000	51109	
45	73	20	-	-	1	48000	105000	2600	4000	51209	
45	73	-	21.3	-	1	48000	105000	2600	4000	53209	
45	73	-	21.3	24	1	48000	105000	2600	4000	53209U	
45	85	28	-	-	1	80500	163000	2000	3000	51309	
45	85	-	30.1	-	1	80500	163000	2000	3000	53309	
45	85	-	30.1	33	1	80500	163000	2000	3000	53309U	
45	100	39	-	-	1.1	128000	246000	1600	2400	51409	
45	100	-	42.4	-	1.1	128000	246000	1600	2400	53409	
45	100	-	42.4	46	1.1	128000	246000	1600	2400	53409U	
50	70	14	-	-	0.6	29000	75500	3200	4800	51110	
50	78	22	-	-	1	49000	111000	2400	3600	51210	
50	78	-	23.5	-	1	49000	111000	2400	3600	53210	
50	78	-	23.5	26	1	49000	111000	2400	3600	53210U	
50	95	31	-	-	1.1	97500	202000	1800	2800	51310	
50	95	-	34.3	-	1.1	97500	202000	1800	2800	53310	
50	95	-	34.3	37	1.1	97500	202000	1800	2800	53310U	
50	110	43	-	-	1.5	147000	288000	1400	2200	51410	
50	110	-	45.6	-	1.5	147000	288000	1400	2200	53410	
50	110	-	45.6	50	1.5	147000	288000	1400	2200	53410U	
55	78	16	-	-	0.6	35000	93000	2800	4300	51111	
55	90	25	-	-	1	70000	159000	2200	3200	51211	
55	90	-	27.3	-	1	70000	159000	2200	3200	53211	
55	90	-	27.3	30	1	70000	159000	2200	3200	53211U	
55	105	35	-	-	1.1	115000	244000	1600	2400	51311	
55	105	-	39.3	-	1.1	115000	244000	1600	2400	53311	
55	105	-	39.3	42	1.1	115000	244000	1600	2400	53311U	
55	120	48	-	-	1.5	181000	350000	1300	1900	51411	
55	120	-	50.5	-	1.5	181000	350000	1300	1900	53411	
55	120	-	50.5	55	1.5	181000	350000	1300	1900	53411U	

Thrust Bearings

└ Single-Direction Thrust Ball Bearings

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min ⁻¹)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>T</i>	<i>T</i> ₃	<i>T</i> ₄	<i>r</i> min.	<i>C</i> _a	<i>C</i> _{0a}	Grease	Oil		
60	85	17	-	-	1	41500	113000	2600	4000	51112	
60	95	26	-	-	1	71500	169000	2000	3000	51212	
60	95	-	28	-	1	71500	169000	2000	3000	53212	
60	95	-	28	31	1	71500	169000	2000	3000	53212U	
60	110	35	-	-	1.1	119000	263000	1600	2400	51312	
60	110	-	38.3	-	1.1	119000	263000	1600	2400	53312	
60	110	-	38.3	42	1.1	119000	263000	1600	2400	53312U	
60	130	51	-	-	1.5	202000	395000	1200	1800	51412	
60	130	-	54	-	1.5	202000	395000	1200	1800	53412	
60	130	-	54	58	1.5	202000	395000	1200	1800	53412U	
65	90	18	-	-	1	42000	117000	2400	3800	51113	
65	100	27	-	-	1	75500	189000	1900	2800	51213	
65	100	-	28.7	-	1	75500	189000	1900	2800	53213	
65	100	-	28.7	32	1	75500	189000	1900	2800	53213U	
65	115	36	-	-	1.1	123000	282000	1500	2400	51313	
65	115	-	39.4	-	1.1	123000	282000	1500	2400	53313	
65	115	-	39.4	43	1.1	123000	282000	1500	2400	53313U	
65	140	56	-	-	2	234000	495000	1100	1700	51413	
65	140	-	60.2	-	2	234000	495000	1100	1700	53413	
65	140	-	60.2	65	2	234000	495000	1100	1700	53413U	
70	95	18	-	-	1	43500	127000	2400	3600	51114	
70	105	27	-	-	1	74000	189000	1900	2800	51214	
70	105	-	28.8	-	1	74000	189000	1900	2800	53214	
70	105	-	28.8	32	1	74000	189000	1900	2800	53214U	
70	125	40	-	-	1.1	137000	315000	1400	2000	51314	
70	125	-	44.2	-	1.1	137000	315000	1400	2000	53314	
70	125	-	44.2	48	1.1	137000	315000	1400	2000	53314U	
70	150	60	-	-	2	252000	555000	1000	1500	51414	
70	150	-	63.6	-	2	252000	555000	1000	1500	53414	
70	150	-	63.6	69	2	252000	555000	1000	1500	53414U	
75	100	19	-	-	1	43500	131000	2200	3400	51115	
75	110	27	-	-	1	78000	209000	1800	2800	51215	
75	110	-	28.3	-	1	78000	209000	1800	2800	53215	
75	110	-	28.3	32	1	78000	209000	1800	2800	53215U	
75	135	44	-	-	1.5	159000	365000	1300	1900	51315	
75	135	-	48.1	-	1.5	159000	365000	1300	1900	53315	
75	135	-	48.1	52	1.5	159000	365000	1300	1900	53315U	
75	160	65	-	-	2	254000	560000	950	1400	51415	
75	160	-	69	-	2	254000	560000	950	1400	53415	
75	160	-	69	75	2	254000	560000	950	1400	53415U	
80	105	19	-	-	1	45000	141000	2200	3400	51116	
80	115	28	-	-	1	79000	218000	1800	2600	51216	
80	115	-	29.5	-	1	79000	218000	1800	2600	53216	
80	115	-	29.5	33	1	79000	218000	1800	2600	53216U	
80	140	44	-	-	1.5	164000	395000	1300	1900	51316	

Thrust Bearings

└ Single-Direction Thrust Ball Bearings

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min ⁻¹)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>T</i>	<i>T</i> ₃	<i>T</i> ₄	<i>r</i> min.	<i>C</i> _a	<i>C</i> _{0a}	Grease	Oil		
80	140	-	47.6	-	1.5	164000	395000	1300	1900	53316	
80	140	-	47.6	52	1.5	164000	395000	1300	1900	53316U	
80	170	68	-	-	2.1	272000	620000	900	1300	51416	
80	170	-	72.2	-	2.1	272000	620000	900	1300	53416	
80	170	-	72.2	78	2.1	272000	620000	900	1300	53416U	
85	110	19	-	-	1	46500	150000	2200	3200	51117	
85	125	31	-	-	1	96000	264000	1600	2400	51217	
85	125	-	33.1	-	1	96000	264000	1600	2400	53217	
85	125	-	33.1	37	1	96000	264000	1600	2400	53217U	
85	150	49	-	-	1.5	207000	490000	1100	1700	51317	
85	150	-	53.1	-	1.5	207000	490000	1100	1700	53317	
85	150	-	53.1	58	1.5	207000	490000	1100	1700	53317U	
85	180	72	-	-	2.1	310000	755000	850	1300	51417X	
85	180	-	77	-	2.1	310000	755000	850	1300	53417X	
85	180	-	77	83	2.1	310000	755000	850	1300	53417XU	
90	120	22	-	-	1	60000	190000	1900	3000	51118	
90	135	35	-	-	1.1	114000	310000	1400	2200	51218	
90	135	-	38.5	-	1.1	114000	310000	1400	2200	53218	
90	135	-	38.5	42	1.1	114000	310000	1400	2200	53218U	
90	155	50	-	-	1.5	214000	525000	1100	1700	51318	
90	155	-	54.6	-	1.5	214000	525000	1100	1700	53318	
90	155	-	54.6	59	1.5	214000	525000	1100	1700	53318U	
90	190	77	-	-	2.1	330000	825000	800	1200	51418X	
90	190	-	81.2	-	2.1	330000	825000	800	1200	53418X	
90	190	-	81.2	88	2.1	330000	825000	800	1200	53418XU	
100	135	25	-	-	1	86000	268000	1700	2600	51120	
100	150	38	-	-	1.1	135000	375000	1300	2000	51220	
100	150	-	40.9	-	1.1	135000	375000	1300	2000	53220	
100	150	-	40.9	45	1.1	135000	375000	1300	2000	53220U	
100	170	55	-	-	1.5	239000	595000	1000	1500	51320	
100	170	-	59.2	-	1.5	239000	595000	1000	1500	53320	
100	170	-	59.2	64	1.5	239000	595000	1000	1500	53320U	
100	210	85	-	-	3	370000	985000	710	1100	51420X	
100	210	-	90	-	3	370000	985000	710	1100	53420X	
100	210	-	90	98	3	370000	985000	710	1100	53420XU	
110	145	25	-	-	1	88000	288000	1700	2400	51122	
110	160	38	-	-	1.1	136000	395000	1300	1900	51222	
110	160	-	40.2	-	1.1	136000	395000	1300	1900	53222	
110	160	-	40.2	45	1.1	136000	395000	1300	1900	53222U	
110	190	63	-	-	2	282000	755000	900	1300	51322X	
110	190	-	67.2	-	2	282000	755000	900	1300	53322X	
110	190	-	67.2	72	2	282000	755000	900	1300	53322XU	
110	230	95	-	-	3	415000	1150000	630	950	51422X	
110	230	-	99.7	-	3	415000	1150000	630	950	53422X	
110	230	-	99.7	109	3	415000	1150000	630	950	53422XU	

Thrust Bearings

└ Single-Direction Thrust Ball Bearings

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min ⁻¹)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>T</i>	<i>T</i> ₃	<i>T</i> ₄	<i>r</i> min.	<i>C</i> _a	<i>C</i> _{0a}	Grease	Oil		
120	155	25	-	-	1	90000	310000	1600	2400	51124	
120	170	39	-	-	1.1	141000	430000	1200	1800	51224	
120	170	-	40.8	-	1.1	141000	430000	1200	1800	53224	
120	170	-	40.8	46	1.1	141000	430000	1200	1800	53224U	
120	210	70	-	-	2.1	330000	930000	800	1200	51324X	
120	210	-	74.1	-	2.1	330000	930000	800	1200	53324X	
120	210	-	74.1	80	2.1	330000	930000	800	1200	53324XU	
120	250	102	-	-	4	480000	1400000	600	900	51424X	
120	250	-	107.3	-	4	480000	1400000	600	900	53424X	
120	250	-	107.3	118	4	480000	1400000	600	900	53424XU	
130	170	30	-	-	1	105000	350000	1400	2000	51126	
130	190	45	-	-	1.5	183000	550000	1100	1600	51226X	
130	190	-	47.9	-	1.5	183000	550000	1100	1600	53226X	
130	190	-	47.9	53	1.5	183000	550000	1100	1600	53226XU	
130	225	75	-	-	2.1	350000	1030000	750	1100	51326X	
130	225	-	80.3	-	2.1	350000	1030000	750	1100	53326X	
130	225	-	80.3	86	2.1	350000	1030000	750	1100	53326XU	
130	270	110	-	-	4	525000	1590000	530	800	51426X	
130	270	-	115.2	-	4	525000	1590000	530	800	53426X	
130	270	-	115.2	128	4	525000	1590000	530	800	53426XU	
140	180	31	-	-	1	107000	375000	1300	2000	51128X	
140	200	46	-	-	1.5	186000	575000	1000	1500	51228X	
140	200	-	48.6	-	1.5	186000	575000	1000	1500	53228X	
140	200	-	48.6	55	1.5	186000	575000	1000	1500	53228XU	
140	240	80	-	-	2.1	370000	1130000	670	1000	51328X	
140	240	-	84.9	-	2.1	370000	1130000	670	1000	53328X	
140	240	-	84.9	92	2.1	370000	1130000	670	1000	53328XU	
140	280	112	-	-	4	550000	1750000	530	800	51428X	
140	280	-	117	-	4	550000	1750000	530	800	53428X	
140	280	-	117	131	4	550000	1750000	530	800	53428XU	
150	190	31	-	-	1	110000	400000	1300	1900	51130X	
150	215	50	-	-	1.5	238000	735000	950	1400	51230X	
150	215	-	53.3	-	1.5	238000	735000	950	1400	53230X	
150	215	-	53.3	60	1.5	238000	735000	950	1400	53230XU	
150	250	80	-	-	2.1	380000	1200000	670	1000	51330X	
150	250	-	83.7	-	2.1	380000	1200000	670	1000	53330X	
150	250	-	83.7	92	2.1	380000	1200000	670	1000	53330XU	
150	300	120	-	-	4	620000	2010000	480	710	51430X	
150	300	-	125.9	-	4	620000	2010000	480	710	53430X	
150	300	-	125.9	140	4	620000	2010000	480	710	53430XU	
160	200	31	-	-	1	113000	425000	1200	1900	51132X	
160	225	51	-	-	1.5	249000	805000	900	1400	51232X	
160	225	-	54.7	-	1.5	249000	805000	900	1400	53232X	
160	225	-	54.7	61	1.5	249000	805000	900	1400	53232XU	
160	270	87	-	-	3	475000	1570000	600	900	51332X	

Thrust Bearings

└ Single-Direction Thrust Ball Bearings

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min ⁻¹)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>T</i>	<i>T</i> ₃	<i>T</i> ₄	<i>r</i> min.	<i>C</i> _a	<i>C</i> _{0a}	Grease	Oil		
160	270	-	91.7	-	3	475000	1570000	600	900	53332X	
160	270	-	91.7	100	3	475000	1570000	600	900	53332XU	
160	320	130	-	-	5	650000	2210000	450	670	51432X	
160	320	-	135.3	-	5	650000	2210000	450	670	53432X	
160	320	-	135.3	150	5	650000	2210000	450	670	53432XU	
170	215	34	-	-	1.1	135000	510000	1100	1700	51134X	
170	240	55	-	-	1.5	280000	915000	850	1300	51234X	
170	240	-	58.7	-	1.5	280000	915000	850	1300	53234X	
170	240	-	58.7	65	1.5	280000	915000	850	1300	53234XU	
170	280	87	-	-	3	465000	1570000	600	900	51334X	
170	280	-	91.3	-	3	465000	1570000	600	900	53334X	
170	280	-	91.3	100	3	465000	1570000	600	900	53334XU	
170	340	135	-	-	5	715000	2480000	430	630	51434X	
170	340	-	141	-	5	715000	2480000	430	630	53434X	
170	340	-	141	156	5	715000	2480000	430	630	53434XU	
180	225	34	-	-	1.1	136000	530000	1100	1700	51136X	
180	250	56	-	-	1.5	284000	955000	800	1200	51236X	
180	250	-	58.2	-	1.5	284000	955000	800	1200	53236X	
180	250	-	58.2	66	1.5	284000	955000	800	1200	53236XU	
180	300	95	-	-	3	480000	1680000	560	850	51336X	
180	300	-	99.3	-	3	480000	1680000	560	850	53336X	
180	300	-	99.3	109	3	480000	1680000	560	850	53336XU	
180	360	140	-	-	5	750000	2730000	400	600	51436X	
180	360	-	148.3	-	5	750000	2730000	400	600	53436X	
180	360	-	148.3	164	5	750000	2730000	400	600	53436XU	
190	240	37	-	-	1.1	172000	655000	1000	1600	51138X	
190	270	62	-	-	2	320000	1110000	750	1100	51238X	
190	270	-	65.7	-	2	320000	1110000	750	1100	53238X	
190	270	-	65.7	73	2	320000	1110000	750	1100	53238XU	
190	320	105	-	-	4	550000	1960000	500	750	51338X	
190	320	-	111	-	4	550000	1960000	500	750	53338X	
190	320	-	111	121	4	550000	1960000	500	750	53338XU	
200	250	37	-	-	1.1	173000	675000	1000	1500	51140X	
200	280	62	-	-	2	315000	1110000	710	1100	51240X	
200	280	-	65.3	-	2	315000	1110000	710	1100	53240X	
200	280	-	65.3	74	2	315000	1110000	710	1100	53240XU	
200	340	110	-	-	4	600000	2220000	480	710	51340X	
200	340	-	118.4	-	4	600000	2220000	480	710	53340X	
200	340	-	118.4	130	4	600000	2220000	480	710	53340XU	
220	270	37	-	-	1.1	179000	740000	950	1500	51144X	
220	300	63	-	-	2	325000	1210000	670	1000	51244X	
220	300	-	65.6	-	2	325000	1210000	670	1000	53244X	
220	300	-	65.6	75	2	325000	1210000	670	1000	53244XU	
240	300	45	-	-	1.5	229000	935000	850	1200	51148X	
240	340	78	-	-	2.1	420000	1650000	560	850	51248X	

Thrust Bearings

└ Single-Direction Thrust Ball Bearings

Boundary Dimensions (mm)						Basic Load Ratings (N)		Limiting Speeds (min ⁻¹)		Bearing Numbers	NSKHPS
<i>d</i>	<i>D</i>	<i>T</i>	<i>T</i> ₃	<i>T</i> ₄	<i>r</i> min.	<i>C</i> _a	<i>C</i> _{0a}	Grease	Oil		
240	340	-	81.6	-	2.1	420000	1650000	560	850	53248X	
240	340	-	81.6	92	2.1	420000	1650000	560	850	53248XU	
260	320	45	-	-	1.5	233000	990000	800	1200	51152X	
260	360	79	-	-	2.1	435000	1800000	560	850	51252X	
260	360	-	82.8	-	2.1	435000	1800000	560	850	53252X	
260	360	-	82.8	93	2.1	435000	1800000	560	850	53252XU	
280	350	53	-	-	1.5	315000	1310000	710	1000	51156X	
280	380	80	-	-	2.1	450000	1950000	530	800	51256X	
280	380	-	85	-	2.1	450000	1950000	530	800	53256X	
280	380	-	85	94	2.1	450000	1950000	530	800	53256XU	
300	380	62	-	-	2	360000	1560000	600	900	51160X	
300	420	95	-	-	3	540000	2410000	450	670	51260X	
300	420	-	100.5	-	3	540000	2410000	450	670	53260X	
300	420	-	100.5	112	3	540000	2410000	450	670	53260XU	
320	400	63	-	-	2	365000	1660000	600	900	51164X	
320	440	95	-	-	3	585000	2680000	450	670	51264X	
320	440	-	100.5	-	3	585000	2680000	450	670	53264X	
320	440	-	100.5	112	3	585000	2680000	450	670	53264XU	
340	420	64	-	-	2	375000	1760000	560	850	51168X	
340	460	96	-	-	3	595000	2800000	430	630	51268X	
340	460	-	100.3	-	3	595000	2800000	430	630	53268X	
340	460	-	100.3	113	3	595000	2800000	430	630	53268XU	
360	440	65	-	-	2	385000	1860000	560	800	51172X	
360	500	110	-	-	4	705000	3500000	380	560	51272X	
360	500	-	116.7	-	4	705000	3500000	380	560	53272X	
360	500	-	116.7	130	4	705000	3500000	380	560	53272XU	